

# The Evaluation of Changes in Concrete Properties Due to Fabric Formwork

by Farhoud Delijani

## ABSTRACT

Fabric as a flexible formwork for concrete is an alternative giving builders, engineers, and architects the ability to form virtually any shape. This technique produces a superb concrete surface quality which requires no further touch up or finishing. Woven polyolefin fabrics are recommended for this application. A permeable woven fabric allows excess water from the concrete mix to bleed through the mold wall, and therefore reduce the water-cement ratio of the concrete mix. Due to the reduction in water-cement ratio, higher compressive strength in fabric formed concrete may be achieved, as also suggested by earlier research. The current research study was conducted to investigate and document the changes in concrete strength and overall quality due to use of commercially available woven polyolefin fabrics. Use of fabric formwork will contribute to decreased construction cost, construction waste, and greenhouse gas emissions. Two sets of tests were conducted as a part of this research study including comparison of compressive strength of fabric formed versus PVC formed concrete cylinders and comparison of behaviour of the fabric formed reinforced columns versus cardboard formed reinforced concrete columns. Variables in this research were limited to two types of fabric with different permeability (Geotex 104F and Geotex 315ST) and two types of concrete; concrete made with conventional Portland cement and no flyash herein called normal concrete (NC) and concrete with 30 percent flyash in its mix design (FAC).

The laboratory results revealed that fabric Geotex 315ST is an ideal geotextile for forming concrete. It was also found that the effects of fabric formwork on concrete quality in a large member are limited mostly to the surface zone and the core of the concrete remains the same as a conventionally formed concrete. Even though fabric formed cylinder tests showed an average of 15% increase in compressive strength of the concrete samples, compressive strength of the reinforced columns did not dramatically change when compared to the companion cardboard formed control columns. This research confirmed that fabric formwork is structurally safe alternative for forming reinforced concrete columns.

## TABLE

### INTRODUCTION

Background and History  
Previous Studies Using  
Permeable Rigid Formwork  
Previous Studies Using Fabric  
Formwork  
Objectives and Scope  
[SELECTION of FABRICS](#)  
Choice of Fabrics  
Fabric Tests Using Normal  
Concrete  
Fabric Tests Using 30% Flyash  
Concrete  
Results  
[PLACING and HANDLING of  
FABRIC-FORMED CONCRETE](#)  
Depth of Bleeding Effect  
Fabrication of Fabric Molds  
Bleeding Tests  
Test Results  
Finish Effect of Vibration on  
Concrete Surface

## OF

### STRENGTH TESTS

Casting and Testing Concrete  
Cylinders with Fabric Formwork  
Density  
Strength Test Results

### COLUMN TESTS

Column Specifications and  
Design  
Column Casting  
Formwork  
Concrete  
Test Setup and  
Instrumentation  
Companion Control Cylinders  
Schmidt Hammer Tests  
Column Compression Tests  
Test Results  
Failure Patterns  
Compressive Strength  
Lessons Learned About Fabric  
Formwork

## CONTENTS

### SUMMARY and CONCLUSIONS

Summary  
Conclusions  
Suggestions for Future Studies

### LIST of SYMBOLS

Additional References

### APPENDICES

[Appendix A](#): Cost Analysis  
[Appendix B](#): Mechanical Press  
Apparatus Weight Calculations  
[Appendix C](#): Results from  
Rebound Tests (Schmidt  
Hammer Tests)  
[Appendix D](#): Summary of  
Calculations and General  
Assumptions in Column Design  
Reinforcement Design  
Maximum Axial Load  
[Appendix E](#): All Columns Test  
Result Curves

## External Links

[The Centre for Architectural Structures and Technology \(C.A.S.T.\)](#)



From:  
<http://fabric-formedconcrete.com/> - **fabric-formedconcrete**

Permanent link:  
<http://fabric-formedconcrete.com/doku.php?id=fabformwiki:research:canada:delijani>

Last update: **2023/10/19 15:01**

